


# DIFFUSED ON BOARD FLEXIBLE LED TAPE

## TUNEABLE DOB



16W/M



up to  
800LM/M



IP20



IP67




Recycleable  
Cardboard



Tuneable



>90Ra



50mm  
Cut Points



Flicker Free

2700K

4000K

6500K

### FEATURES

- CCT Tuneable 2700K ~ 6500K
- Industrial grade adhesive backing tape
- Supplied on cardboard reels
- High CRI >90Ra
- Working temperature -20°C - +40°C
- High efficacy
- 3 years warranty

### SPECIFICATIONS

Stock Code	1223-493	1102-484
Part Code	DOB-640-TN-20	DOB-640-TN-67
Voltage	24VDC	24VDC
Power Consumption	16W/M	16W/M
Lumen Output	720~800LM/M	720~800LM/M
Efficacy	50LM/W	50LM/W
Tone (CCT)	2700K ~ 6500K	2700K ~ 6500K
LED/metre	640	640
LED Pitch	1.54mm	1.54mm
Cut Points	50mm	50mm
CRI	>90Ra	>90Ra
IP Rating	20	67
Dimensions	5000 x 10 x 1.6mm	5000 x 12 x 1.8mm



2500K



4000K



6000K

# DIFFUSED ON BOARD FLEXIBLE LED TAPE

# TUNEABLE DOB



## COMPATIBILITY



## CONTROL METHODS

- Remote Control - CCT-RF-RCX (with a receiver CCT-RF-3X5A)
- Bluetooth (Apps, Voice Control) - BLE-15A-CCT
- Hard-wired wall-mounted controller - CCT-4X5A-WM

## SUGGESTED DRIVERS

Up to 3 M	Up to 5 M	Up to 10 M
Power supplied from ONE end	Power supplied from ONE end	Power supplied from the MIDDLE
PCV2450-REV-A (IP20)	PCV24101-REV-A (IP20)	PCV24200E-REV-A (IP67)
PCV2475E-REV-A (IP67)	PCV24100E-REV-A (IP67)	PCV24200E-REV-A (IP67)

## MECHANICAL DIAGRAM

