

Wall Pack Series



Key Features:

- Robust fixture with die-cast Aluminium alloy housing
- Improved corrosion protection - C4-M
- IK10, IP66 Ratings
- 4 Power adjustable: 30% - 50% - 75% - 100%
- Light Coverage: 180° or 360°
- Lifetime up to 153,000 hrs @Ta = 25°C
- CCT Selectable - 4000K factory default with 3000 & 5000k available via dip switches

PFBW SPECIFICATION

Part Code	PFBW-14-3C-VO	PFBW-25-3C-VO
Input Voltage	220 ~ 240 VAC	
Frequency	50 ~ 60 Hz	
Efficiency	90 lm/W	
Lumen Output	1260lm	2250lm
Light Coverage	360°	
Power Factor	>0.9	
Current	350mA	600mA
Power	14W	25W
Surge Protection	4kV line-line, 6kV line-earth	
Driver Type	Constant Current (CC)	
Control	Non-dimmable / Dimmable / DALI	
Color Temperature	4000K (3000K & 5000K selectable)	
Color Rendering Index	Ra70 (Ra80 optional)	
Lens Type	Polycarbonate	
Fixture Color	Black (RAL9017)	
Material	Die-cast Aluminium Alloy	
Operating Temperature	-30°C ~ + 45°C	
Weight	2.9 Kgs	
Dimensions	φ203 x 256 mm	



PowerLed (UK) Ltd
Orion House
Calleva Park
Aldermaston
Berkshire
RG7 8SN

Contact:
Tel: 0118 9703856
enquiries@powerled.uk.com
www.powerled.uk.com

