

IDIS LED WALL PACK

Designed with robust aluminium housing and IK10 impact tested.



Eyelid cover designed to reduce glare when position at low level.



Opaque diffuser

The IDIS exterior wall pack has a compact design and comes in 4 sizes and with a range of lumen outputs from 650~1400lm. The IDI-1500 & IDI-C1500 models are offered with a microwave sensor for presence detection and 3 hour non-maintained self test emergency as options. Ideal for installation in corridors, stairwells and exterior installation, the IDIS is also available with an eyelid version for low level environments.

Product Features

- 120° Light distribution
- Up to 88lm/W
- Ultra robust aluminium design
- IP65 Ingress protected
- Excellent optical design
- Long service life
- Uses less power than fluorescent alternatives
- 3 hour emergency and microwave sensor options available
- Surface and pendant mounting for ease of installation
- Designed for commercial premises and offices, corridors, exterior areas, stairwells, hotel leisure and healthcare environments and social housing

IDI-900S

Power 14W	Input Voltage 220-240V	Beam Angle 120°	CRI >80	Lumen Output 800lm	Fitting Colour Aluminium & Black	Colour 4000K	Part Code IDI-900S
--------------	---------------------------	--------------------	------------	-----------------------	-------------------------------------	-----------------	-----------------------



Dimensions Ø 265 x 90mm

IDI-1500

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-1500S
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	------------------------



Dimensions Ø 365 x 141.5mm

IDI-1500-MS

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-1500S-MS
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	---------------------------



Dimensions Ø 365 x 141.5mm

IDI-1500-EM

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-1500-EM
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	--------------------------



Dimensions Ø 365 x 141.5mm

IDI-1500-MS-EM

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-1500-MS-EM
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	-----------------------------



Dimensions Ø 365 x 141.5mm

IDI-C900S

Power 14W	Input Voltage 220-240V	Beam Angle 120°	CRI >80	Lumen Output 650lm	Fitting Colour Aluminium & Black	Colour 4000K	Part Code IDI-C900S
--------------	---------------------------	--------------------	------------	-----------------------	-------------------------------------	-----------------	------------------------



Dimensions Ø 265 x 96mm



IDI-C1500

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-C1500
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	------------------------



Dimensions Ø 365 x 156mm



IDI-C1500-MS

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-C1500-MS
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	---------------------------



Dimensions Ø 365 x 156mm



IDI-C1500-EM

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-C1500-EM
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	---------------------------



Dimensions Ø 365 x 156mm



IDI-C1500-MS-EM

Power 16W	Input Voltage 200-240V	Beam Angle 120°	CRI >80	Lumen Output 1400lm	Fitting Colour Aluminium & Black	Colour Selectable 3000K, 4000K, 5000K	Part Code IDI-C1500-MS-EM
--------------	---------------------------	--------------------	------------	------------------------	-------------------------------------	---	------------------------------



Dimensions Ø 365 x 156mm

